



Maxprobe™ 120

Datasheet

The Maxprobe™ 120 is the largest reel in the Scanprobe Techniques push-rod camera system family, with a longer and thicker rod for the bigger jobs. With the same user-enhancements and stability features as the rest of the Maxprobe™ range, including a sunlight readable screen and pneumatic tyres, this is the ultimate big brother.



Weight

- Reel 49kg
- Box 5.5kg

Rod Length 120m

Rod Diameter 14mm

Meterage Counter Yes

Voltage 12v DC / 230v AC / 115v AC

Current Ex Power Supply - 1.7A Max

Operating Temp. -10°C - +50°C

Charging Temp. 0°C - 40°C

Battery Li-ion (9hrs running time)

Dimensions

- Reel 1280mm x 840mm x 530mm
- Box 360mm x 290mm x 160mm

LCD Display Size 10.4"

Resolution 800 x 600 RGB (SVGA)

IP Rating

- Reel IP54
- Camera IP68

Sonde Frequency 512Hz / 33kHz Optional

Storage

- 32Gb—1Tb HDD
- 2x USB 2.1 ports
- 1x SD card port
- 1x Ethernet port

Software

- WinCan Embedded
- Bespoke reporting software

Output

800 x 600 SVGA. DE15 socket
WiFi

Video

MPEG4

Image Format

JPEG

