



Maxprobe™

Datasheet

The Maxprobe™ is Scanprobe Techniques' flagship push-rod camera system, designed with the drainage engineer in mind. Not satisfied with just being able to survey pipelines, this camera system is optimised to make the entire process easy, not just when the camera is in the pipe.



Weight	
- Reel	23.5kg
- Box	5.5kg
Rod Length	60m
Rod Diameter	12mm
Meterage Counter	Yes
Voltage	12v DC / 230v AC / 115v AC
Current	Ex Power Supply - 1.7A Max
Operating Temp.	-10°C - +50°C
Charging Temp.	0°C - 40°C
Battery	Li-ion (9hrs running time)
Dimensions	
- Reel	1010mm x 415mm x 625mm
- Box	360mm x 290mm x 160mm
LCD Display Size	10.4"
Resolution	800 x 600 RGB (SVGA)
IP Rating	
- Reel	IP54
- Box	IP68
Sonde Frequency	512Hz / 33kHz Optional
Storage	
	- 32Gb— 1Tb HDD
	- 2x USB 2.1 ports
	- 1x SD card port
	- 1x Ethernet port
Software	
	- WinCan Embedded
	- Bespoke reporting software
Output	800 x 600 SVGA. DE15 socket WiFi
Video	MPEG4
Image Format	JPEG

