



Maxprobe™ 120

Datasheet

The Maxprobe™ 120 is the largest reel in the Scanprobe Techniques push-rod camera system family, with a longer and thicker rod for the bigger jobs. With the same user-enhancements and stability features as the rest of the Maxprobe™ range, including a sunlight readable screen and pneumatic tyres, this is the ultimate big brother.



Weight	
- Reel	49kg
- Box	5.5kg
Rod Length	120m
Rod Diameter	14mm
Meterage Counter	Yes
Voltage	12v DC / 230v AC / 115v AC
Current	Ex Power Supply - 1.7A Max
Operating Temp.	-10°C - +50°C
Charging Temp.	0°C - 40°C
Battery	Li-ion (9hrs running time)
Dimensions	
- Reel	1280mm x 840mm x 530mm
- Box	360mm x 290mm x 160mm
LCD Display Size	10.4"
Resolution	800 x 600 RGB (SVGA)
IP Rating	
- Reel	IP68
- Box	IP54
Sonde	
- Frequency	512Hz / 33kHz Optional
- Location	Camera Head
Storage	
	- 32Gb—1Tb HDD
	- 2x USB 2.1 ports
Software	
	- WinCan Embedded
	- mina reporting software
Output	800 x 600 SVGA. DE15 socket WiFi
Video	MPEG4
Image Format	JPEG

