



Maxprobe™ XL

Datasheet

The Maxprobe™ XL is the 100m version of our signature push-rod camera system, with enhanced features to handle the extended push-reach and rod length, yet still boasting the same functionality and benefits such as all-terrain pneumatic tyres and easy-access rod-braking system.



Weight	
- Reel	38.5kg
- Box	5.5kg
Rod Length	100m
Rod Diameter	12mm
Meterage Counter	Yes
Voltage	12v DC / 230v AC / 115v AC
Current	Ex Power Supply - 1.7A Max
Operating Temp.	-10°C - +50°C
Charging Temp.	0°C - 40°C
Battery	Li-ion (9hrs running time)
Dimensions	
- Reel	660mm x 480mm x 998mm
- Box	360mm x 290mm x 160mm
LCD Display Size	10.4"
Resolution	800 x 600 RGB (SVGA)
IP Rating	
- Reel	IP68
- Box	IP54
Sonde	
- Frequency	512Hz / 33kHz Optional
- Location	Camera Head
Storage	
	- 32Gb—1Tb HDD
	- 2x USB 2.1 ports
Software	
	- WinCan Embedded
	- mina reporting software
Output	
	800 x 600 SVGA. DE15 socket
	WiFi
Video	MPEG4
Image Format	JPEG



WinCan



mina®

Scanprobe Techniques Ltd.
Unit 11, Kenley Trade Park, Old Barn Lane
Kenley, Surrey, CR8 5AU

Tel. (0)203 253 2001
Email. sales@scanprobe.com
Web. www.scanprobe.com